

# ウィットねじ下穴径

- 参考寸法 -

表1 ウィットねじの呼びと下穴径

単位：mm

ねじの呼び	下穴径最小 (ひっかかり率)	ねじ下ぎりの直径	
		A列(硬質材)	B列(軟質材)
W 1/8-40	2.456 (88.4%)	2.65	2.60
5/32-32	3.070 (〃)	3.25	3.20
3/16-24	3.564 (〃)	3.75	3.70
1/4-20	4.914 (88.3%)	5.10	5.00
5/16-18	6.340 (88.4%)	6.60	6.50
3/8-16	7.733 (88.2%)	8.00	7.90
7/16-14	9.048 (88.8%)	9.40	9.30
1/2-12	10.310 (88.2%)	10.70	10.50
9/16-12	11.898 (〃)	12.30	12.00
5/8-11	13.257 (88.5%)	13.70	13.50
3/4-10	16.178 (88.3%)	16.70	16.50
7/8- 9	19.031 (88.4%)	19.50	19.30
1 - 8	21.814 (88.2%)	22.40	22.00
1 1/8- 7	24.469 (88.4%)	25.00	24.80
1 1/4- 7	27.644 (〃)	28.30	28.00
1 3/8- 6	30.123 (88.6%)	30.50	30.30
1 1/2- 6	33.298 (〃)	33.80	33.50
1 5/8- 5	35.529 (88.3%)	36.00	35.70
1 3/4- 5	38.704 (〃)	39.20	39.00
1 7/8- 4 1/2	41.237 (88.4%)	41.80	41.50
2 - 4 1/2	44.412 (〃)	45.00	44.70